

**(19) World Intellectual Property
Organization
International Bureau**



(43) International Publication Date
21 October 2004 (21.10.2004)


PCT

(10) International Publication Number
WO 2004/089799 A1

- | | |
|---|--|
| <p>(51) International Patent Classification⁷: B65H 75/48, H02G 11/02</p> <p>(21) International Application Number: PCT/EP2004/050496</p> <p>(22) International Filing Date: 9 April 2004 (09.04.2004)</p> <p>(25) Filing Language: English</p> <p>(26) Publication Language: English</p> <p>(30) Priority Data: 03100990.5 11 April 2003 (11.04.2003) EP</p> <p>(71) Applicant (for all designated States except US): IPALCO B.V. [NL/NL]; Ohmweg 17, NL-2952 BD Alblasserdam (NL).</p> <p>(72) Inventor; and</p> <p>(75) Inventor/Applicant (for US only): GIESEKE, Christoph [DE/DE]; Hochmeisterstrasse 15, 51065 Köln (DE).</p> <p>(74) Agents: SCHMITT, Armand et al.; Office Ernest T. Freylinger S.A., B.P. 48, L-8001 Strassen (LU).</p> | <p>(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.</p> <p>(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published: — with international search report</p> |
|---|--|

[Continued on next page]

(54) Title: CONSTRUCTION KIT FOR A SPRING-DRIVEN CABLE DRUM



(57) Abstract: A construction kit for a spring-driven cable drum includes a pre-assembled drum core (12) the housing of which constitutes a winding surface for the cable and containing at least one spiral spring (74, 74') and at least one spring anchor hub (80, 80'). The pre-assembled drum core (12) is provided with an axle channel passing right through it but no axle. The spring anchor hub (80, 80') is maintained to all intents and purposes coaxial with this axle channel by the spiral springs (74, 74'). The construction kit further includes a separate axle (16) which can be inserted from either side into the axle channel of the pre-assembled drum core (12), insertion of the axle (16) into the axle channel establishing a form-fit rotary coupling between the spring anchor hub (80, 80') and the axle (16).



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.